# Technical Specifications

| Model SR1205IL | PN220AA |
|---|---|
| **Processor & Speed** | AMD S-2800+ 2.0GHz (T)462 |
| **Chipset** | VIA KM400A |
| **Motherboard** | Kelut-GL6E (A7V8X-LA) |
| **RAM** | 128/3200 MB 400DDR SDRAM (runs@266MHz) |
| Maximum | 2 GB (2x1024MB DDR SDRAM) |
| Sockets | Two 184-pin DDR DIMMs |
| Size | 128, 256, 512  AND 1024 MB DDR DIMMs |
| **Free DIMM Sockets** | One |
| Pairs Required | No |
| Type Supported | JEDEC unbuffered DDR SDRAM DIMM specification |
| **Cache** | 128 KB L1, 256 KB L2 Integrated on Processor module |
| **Hard Drive** | 40 GB (7200 RPM) |
| **CD-ROM Drive** | CD-ROM Drive: 48x maximum speed |
| Access Speed | 75ms |
| Transfer Rate | 7.2 MB/sec |
| **Diskette Drive** | 3.5" (1.44MB) |
| **Fax/Data Modem** | V.90 56Kbps |
| Fax Speed | Up to 14.4Kbps |
| Data Compression | V.42 bis |
| Error Correction | V .42 |
| EIA Fax Commands | Class 1 |
| **Video Graphics** | AGP 8X, Integrated |
| Controller | Integrated w/Via KM400 Chipset |
| Video Memory | 64MB UMA |
| **Network Card** | 10/100 BaseT, Integrated |
| **1394 Card** | IEEE-1394, Integrated |
| **Sound** | AC'97, 6 Channel, Integrated on MB |
| Controller | Realtek ALC658 |
| **Chassis** | Gobi, 250HV PSU |
| **USB Interface Specification** | USB 2.0 |
| **External I/O**   Rear Connectors | 4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone |
| **Expansion Slots (Total)** | 3= PCI, 1=AGP |
| **Expansion Slots (FREE)** | 2= PCI, 1=AGP |
| **Drive Bays (Total)** | Two 5.25" external, One 3.5" external, One 3.5" internal |
| **Drive Bays (FREE)** | One 5.25" external |
| **Keyboard/Mouse** | One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse |